

### Features

- ✧ Low power loss, high efficiency
- ✧ High current capability, low VF
- ✧ High reliability
- ✧ High surge current capability
- ✧ Epitaxial construction
- ✧ Guard-ring for transient protection
- ✧ For use in low voltage, high frequency inverter, free wheeling, and polarity protection application
- ✧ Green compound with suffix "G" on packing code & prefix "G" on datecode



### Mechanical Data

- ✧ Cases: TO-220AB molded plastic
- ✧ Epoxy: UL 94V-0 rate flame retardant
- ✧ Terminals: Pure tin plated, lead free, solderable per MIL-STD-202, Method 208 guaranteed
- ✧ Polarity: As marked
- ✧ High temperature soldering guaranteed: 260°C/10 seconds/.25", (6.35mm) from case
- ✧ Weight: 1.89 grams

### Ordering Information(example)

Part No.	Package	Packing	Packing code	Packing code (Green)
SR1620	TO-220AB	50 / TUBE	C0	C0G

### Maximum Ratings and Electrical Characteristics

Rating at 25 °C ambient temperature unless otherwise specified.

Parameter	Symbol	SR 1620	SR 1630	SR 1640	SR 1650	SR 1660	SR 1690	SR 16100	SR 16150	Units	
Maximum Recurrent Peak Reverse Voltage	V <sub>RRM</sub>	20	30	40	50	60	90	100	150	V	
Maximum RMS Voltage	V <sub>RMS</sub>	14	21	28	35	42	63	70	105	V	
Maximum DC Blocking Voltage	V <sub>DC</sub>	20	30	40	50	60	90	100	150	V	
Maximum Average Forward Rectified Current	I <sub>F(AV)</sub>	16								A	
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I <sub>FSM</sub>	170								A	
Maximum Instantaneous Forward Voltage (Note 1) @ 8 A	V <sub>F</sub>	0.55			0.70		0.90		1.05	V	
Maximum D.C. Reverse Current @ T <sub>A</sub> =25 °C at Rated DC Blocking Voltage @ T <sub>A</sub> =100 °C	I <sub>R</sub>	0.5					0.1			mA	
		15			10		5			mA	
Typical Junction Capacitance (Note 2)	C <sub>j</sub>	440			320					pF	
Typical Thermal Resistance	R <sub>θJC</sub>	2.5								°C/W	
Operating Junction Temperature Range	T <sub>J</sub>	- 65 to + 125					- 65 to + 150				°C
Storage Temperature Range	T <sub>STG</sub>	- 65 to + 150								°C	

Note 1 : Pulse Test with PW=300 usec, 1% Duty Cycle

Note 2 : Measured at 1 MHz and Applied Reverse Voltage of 4.0V D.C.

## RATINGS AND CHARACTERISTIC CURVES (SR1620 THRU SR16150)

FIG. 1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG. 2- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT PER LEG




FIG. 3- TYPICAL FORWARD CHARACTERISTICS PER LEG




FIG. 4- TYPICAL REVERSE CHARACTERISTICS PER LEG




FIG. 5- TYPICAL JUNCTION CAPACITANCE PER LEG





FIG. 6- TYPICAL TRANSIENT THERMAL CHARACTERISTICS




### Ordering information

Part No.	Package	BULK Packing	Packing code	Packing code (Green)
SR16xx	TO-220AB	50 / TUBE	C0	C0G

Note: "xx" is Device Code from "20" thru "150".

### Dimensions



DIM.	Unit(mm)		Unit(inch)	
	Min	Max	Min	Max
A	-	10.50	-	0.413
B	2.62	3.44	0.103	0.135
C	2.80	4.20	0.110	0.165
D	0.68	0.94	0.027	0.037
E	3.54	4.00	0.139	0.157
F	14.60	16.00	0.575	0.630
G	13.19	14.79	0.519	0.582
H	2.41	2.67	0.095	0.105
I	4.42	4.76	0.174	0.187
J	1.14	1.40	0.045	0.055
K	5.84	6.86	0.230	0.270
L	2.20	2.80	0.087	0.110
M	0.35	0.64	0.014	0.025

### Marking Diagram



P/N                = Specific Device Code  
G                 = Green Compound  
YWW             = Date Code

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Taiwan Semiconductor:

[SR1630](#) [SR1650](#) [SR1660](#) [SR1620](#) [SR1640](#) [SR16100](#) [SR16150](#) [SR1690](#)